



OR-T 250

A QUANTUM LEAP IN PLASTIC STRAP TOOLING



Easy to operate
Maximum uptime
Cost-efficient operation

Patent pending

 **ORGAPACK**

OR-T 250



Quantum leap:
Strapping with only one push of a button!



Easy to use

- Semiautomatic and automatic settings
- Light or regular tension adjustment
- Simple one-button operation

Maximum uptime

- Fully or semiautomatic tensioning, welding and strap cutting with the push of one button
- Up to 400 strapping cycles between recharges*

**Number of cycles will vary depending on strap quality, package size and tension.*

Low maintenance

- Brushless motor for less wear and longer life
- Innovative battery design reduces contact damage
- Recharging at any time



An ITW Company

Technical data

Weight (including battery)	8.6 lbs
Dimensions	
– Length	13.15"
– Width	5.43"
– Height	5.83"
Tensioning force	200–560 lbf
– Soft	90–337 lbf
Tensioning speed	8.66"/sec.
Sealing	Friction-weld-seal

Battery charger, battery

Charger voltage	100, 110, 230 V
Battery charging time	20–45 minutes*
No of cycles per battery, up to	400**
Battery: Li-Ion (Bosch)	14.4 V, 2.6 Ah
Plastic strap	Polypropylene (PP)
Polyester (PET)	

Width	1/2", 5/8" (12–13, 15–16 mm)
– Option	3/8" (9–11 mm)
Thickness	.20–.40" (0.5–1.0 mm)

Options

- Suspension bow
- Protection plate
- Protection cover
- Power supply

* After 20 minutes, approx 70% charge capacity

** Depending on strap quality, tension and package



Acme
501 W. Lake Street
Suite 105
Elmhurst, IL 60126
Phone 630-589-5100

www.acme-ds.com
www.acme-packaging.com



Developed and
manufactured
in Switzerland

